

ITEM TECHNICAL CARD



diámetro vite	M4
E (mm)	0,45
G (mm)	6,0
tipo	DGQXX834A
A (mm)	12,2
C (mm)	8,3
B (mm)	12,0
s - spessore lamiera (mm)	1,2 - 1,6
D (mm)	7,2
foro lamiera (mm)	8,3x8,3
F (mm)	12,5

DESCRIZIONE \ DESCRIPTION:					CATEGORIA \ CATEGORY:		4584700.01000		
DadoOX Gab.OX ss1,2-1,6 a.8,3x8,3(834AXX) M4									
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:					NOTE \ NOTES:		
ESEGUITO DA \ DRAWN BY:	DATA:	TRATT. SUPERFICIALE\ SURF. TREATMENT:		Rugosità superficiale generale: General surface roughness:					
RIVIT									
CONTROLLATO DA \ CHECKED BY:	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:			NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW				
RIVIT									
APPROVATO DA \ APPROVED BY:	DATA:	DUREZZA \ HARDNESS:	FOGLIO\ SHEET:	FORMATO FOGLIO:		METODO 1 (ISO 128) METHOD 1 (ISO 128)	REVISIONE: REVISION:		
RIVIT			1 OF 1	SHEET FORMAT:	A4				
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT					
				Mod.P023_07					